

DT2 | DT5 DT2+



www.survey.co.th

* ภาพ: DT2+

DT2+

- Distance Measurement 300m.
- Laser Pointer
- Stake Out Function
- 2 Displays
- Angle accuracy 2"
- Laser Plummet
- Li-on Battery / AA Battery

DT2 / DT5

- 2 Displays
- Angle accuracy 2"/5"
- Laser Plummet
- Li-on Battery / AA Battery

SPECIFICATIONS

TELESCOPIC

Image
Magnification
Effective Aperture
Resolving Power
Field of View
Minimum Focus
Stadia Accuracy
Stadia Ratio
Stadia Constant
Tube Length

DT2+



DT2 / DT5



Erect
30x
40mm
3"
1°30'
1.5m
<0.40%/L
100
0
155mm

ANGLE

Type
Accuracy
Minimum Reading
Detection Method

2"

Absolute Encoding

2"/5"

1"/5"/10"

H: dual; V: dual

DISTANCE

Single Prism Range
Accuracy
Measuring Time
PPM Correction
Prism Constant

300m
3mm+2ppm*D
Continuous: 0.3s; Fine: 1.5s
Manual input, auto correct
Manual input, auto correct

not available

DISPLAY

Display Unit
No. of Displays
Keyboard

2.7", 160*90 dots
2
22 numeric and function keys

2.8", 160*90 dots
2
8 function keys

LASER POINTER

Wavelength
Laser Class
Spot Size
Axis Error

635±20nm
Class II
≤5mm/100m
≤10"

not available

PLUMMET - LASER

Accuracy
Spot Size
Length
Laser Class

1.5mm
2.5mm
635±20nm
Class II

- OPTICAL

Image
Magnification
Focusing Range
Field of View

Erect
3X
0.3m - ∞
5°

LEVEL

Plate Level
Circular Level

8"/2mm
30"/2mm

POWER SUPPLY

Battery
Voltage
Working Time

Li-on battery 2,000mAh / AA battery
7.4V
8h

PHYSICAL

Working Temperature
Size
Weight

-20°C to 50°C
165*160*340mm
4.7kg



บริษัท เอส.ดี.เอ็ม. จำกัด

1/285 หมู่ 9 ต.บางพลู อ.ปากเกร็ด จ.นนทบุรี 11120

Ins. 02 582 3509 Line id : @SDMthailand

www.survey.co.th



@SDMTHAILAND